



**Specifications Ledvance LED Panel  
Compact 33W 3630lm - 840 Cool White  
| 60x60cm - UGR <19 - Dali Dimmable**

[View Product](#)

## General Information

|                          |                                |
|--------------------------|--------------------------------|
| SKU                      | 247046                         |
| EAN                      | 4099854017261                  |
| manufacturer_code        | 4099854017261                  |
| Brand                    | Ledvance                       |
| Manufacturer Name        | PL COMP 600 V 33W 840 U19 DALI |
| Any Lamp all-in warranty | 5 Years                        |
| Average Lifetime (h)     | 50000                          |
| Series                   | PANEL COMPACT                  |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 33W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light Colour Options        | Single Color       |

|                        |                            |
|------------------------|----------------------------|
| Including bulb         | Yes                        |
| Luminous Flux (Lumen)  | 3630lm                     |
| Lumen per watt         | 110                        |
| Impact Protection (IK) | IK02 - 0.20 joule          |
| Fixture Connection     | Screwless terminal, 4-Pole |
| Finish of Reflector    | Frosted                    |
| Product Type Category  | LED Panel                  |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +45                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 32      |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process