



**Specifications Philips LED Downlight  
Coreline DN142B Aluminium White  
20.5W 2350lm 120D - 840 Cool White |  
Cutout 200mm - IP20 - DALI Dimmable  
- White Reflector**

[View Product](#)

## General Information

|                          |                         |
|--------------------------|-------------------------|
| SKU                      | 248715                  |
| EAN                      | 8720169108998           |
| manufacturer_code        | 8720169108998           |
| Brand                    | Philips                 |
| Manufacturer Name        | DN142B 20S/840 PSD-E WR |
| Any Lamp all-in warranty | 5 Years                 |
| Average Lifetime (h)     | 50000                   |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x18               |
| Wattage                     | 20.5W              |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |

|                       |                                    |
|-----------------------|------------------------------------|
| Light Colour Options  | Single Color                       |
| Beam Angle (degree)   | 60                                 |
| Luminous Flux (Lumen) | 2350lm                             |
| Lumen per watt        | 120                                |
| Power factor          | >0.95                              |
| Unified Glare Rating  | < 25 - for hallways and staircases |
| Optical Cover         | PC (Polycarbonate)                 |
| Product Type Category | LED Downlight                      |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| EOC8                   | 10899800                      |
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-Rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 6-pole] |
| Series                 | DN142B                        |

## Dimensions

Height (mm)

**Why Any-lamp?**

105

Diameter (mm)

216



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

Type of sensor

No Sensor

